HOT/COLD FOOD TRANSPORTERS













IFT-1D (INCLUDES STRAP)
Can also be used with IFPC-series

- Molded with polypropylene and insulated with polyurethane foam to maintain safe food serving temperatures for hours without the use of electricity or sterno
- Adjustable vent cap equalizes outside and inside compartment pressure for easy lid opening
- Stackable and interlockable for easy storage, and space saving
- Standard food service pans are easy to load and remove
- Easy-to-clean holding compartments
- NSF listed

	ITEM	DESCRIPTION	UOM	CASE
	IFT-1	Single Insulated Food Pan Cart, NSF	Set	1
*	IFT-2	Double Insulated Food Pan Cart, Built-In Dolly	Set	1
	IFT-1D	Dolly w/Cargo Strap for IFC-1	Set	1
	IFT-C5	5" Caster for IFT-2	Each	1
	IFT-C5B	5" Brake Caster for IFT-2	Each	1

Additional Information

ITEM	DIMENSIONS	COMPARTMENT CAPACITY		
IFT-1	Exterior Dimensions: 18-3/4"W x 26-3/4"D x 24-1/2"H Interior Dimensions: 13-1/4"W x 21"D x 19-5/16"H	6 Full-Size, 2.5" H 4 Full-Size, 4" H 3 Full-Size, 6" H 4 Half-Size, 6" H	8 Half-Size, 4" H 9 1/3 Size, 6" H 12 1/3 Size, 4" H 6 1/3 Size, 8" H	
IFT-2	Exterior Dimensions: 20"W x 27-1/2"D x 47-1/4"H Interior Dimensions for Each Compartment: 13-1/4"W x 21"D x 17"H	Each of the two compartments: 4 Full-Size, 2-1/2" H 3 Full-Size, 4" H 2 Full-Size, 6" H 10 Half-Size, 2-1/2" H	Can hold the following pans: 6 Half-Size, 4" H 4 Half-Size 6" H 6 1/3rd Size, 6" H 9 1/3rd Size, 4" H	
IFT-1D		Use with IFT-1		

HOT IFT	188°F	184°F	179°F	175.5°F	171.5°F
IFPC	188°F	184.5°F	181.5°F	179°F	176F
	Starting	1 hour	2 hours	3 hours	4 hours
COLD	Temperature				
IFT	33.8°F	34.6°F	35.4°F	36.3°F	37.1°F
IFPC	32°F	33°F	34°F	35.5°F	36.5°F
	Starting Temperature	1 hour	2 hours	3 hours	4 hours

